

# SCK0TTL26-3.5 T Type Calibration Kit

(DC - 26.5GHz / 3.5mm)

## Key Features

- Frequency Range: DC to 26.5GHz
- VSWR : <1.065
- Phase Deviation:  $\pm 2.0^\circ$
- Calibration standards to perform full two-port calibration



## Overview

Saluki's SCK0TTL26-3.5 series mechanical calibration kit has been designed to provide superior measurement results when used with precision instruments. It is designed for use in both field and lab environments. It is a high precision component and should be handled with proper care. Excessive shock, torque, or power should be avoided to prevent permanent damage.

Type	Model	Frequency	Spec.	Connector	Qty.
T	SCK0TTL26-3.5(M)	DC - 26.5GHz	Open: $\pm 2.0^\circ$ Short: $\pm 2.0^\circ$ Load: VSWR<1.065	3.5mm (Male)	1
	SCK0TTL26-3.5(F)			3.5mm (Female)	1

## Material Information

Basic Data	
Interface	IEEE Std 287
Mating Cycles	>500 cycles

Electrical Data	
Frequency	DC - 26.5GHz
Impedance	50 $\Omega$
Average Power	$\leq 0.5$ W

Operating Temperature	Storage Temperature
-10 $^\circ$ C to +55 $^\circ$ C	-50 $^\circ$ C to +70 $^\circ$ C

No.367, Fuxing N. Rd.,105 Taipei,Taiwan Tel: +886. 909 602 109

sales@salukitec.com [www.salukitec.com](http://www.salukitec.com)

