

# SK300 Handheld Optical Power Meter

Wavelength range: 800 - 1700nm



## Key Features

- Support linear mW and nonlinear index dBm simultaneous display
- Support single and multiple mode fibers
- Support automatic shutdown and zeroing
- Support backlight selection
- Support user self-calibration
- Support FC, SC, and ST interfaces

Saluki Handheld Optical Power Meter (H-OPM) is mainly used for continuous optical signal power measurement, low power microprocessor is used for control. The H-OPM has the advantages of fully functional and reliable performance. Widely used in optical fiber construction and maintenance, optical fiber communication, optical fiber sensing, optical CATV and other fields. Instrument mould adopts advanced cold shell molding process, beautiful and durable, instrument mould design meets ergonomic requirements. The H-OPM uses the built-in detector, which can be protected well. With a small shape, you can choose the backlight display and automatic shutdown function, with ultra wide optical power testing range.

No.367, Fuxing N. Rd.,105 Taipei,Taiwan Tel: +886.909 602 109

sales@salukitec.com [www.salukitec.com](http://www.salukitec.com)



# SK300 Handheld Optical Power Meter

Wavelength range: 800 - 1700nm

## Technical Specifications

Parameters	Specifications
Wavelength range	800nm - 1700nm
Optical connector	Universal FC/SC/ST
Detector type	InGaAs
Measurement range	-70dBm to +6dBm, or -50dBm to +26dBm
Uncertainty	±5%
Standard wavelength	850/980/1300/1310/1490/1550/1625/1650nm
Display resolution	mW: 0.1%, dBm: 0.01dBm
Working temperature	-10°C to +50°C
Storage temperature	-40°C to +70°C
Auto off time	10 min
Battery continuous operating time	≥120 h
Size	186mm*100mm*50mm
Power	Three AA batteries / 1500mAh Lithium battery (optional)
Instrument net weight	140g / 150g

## Standard Package

Item	Name	Qty
1	SK300 host	1 Unit
2	SC adapter	1 PC